

*approved
for entry
CJ
2/18/06*

List of Claims

1. (previously presented) A solenoid carrier assembly comprising:
a carrier with a top surface separated from a bottom surface by a side surface;
a stator assembly attached to said carrier and including an exposed bottom surface; and
a deflection cavity having a carrier centerline passing therethrough and being disposed in said carrier between said top surface and said stator assembly.
2. (previously presented) A solenoid carrier assembly comprising:
a carrier with a top surface separated from a bottom surface by a side surface;
a stator assembly attached to said carrier and including an exposed bottom surface;
a deflection cavity disposed in said carrier between said top surface and said stator assembly; and
said bottom surface of said stator assembly is flush with said bottom surface of said carrier.
3. (previously presented) A solenoid carrier assembly comprising:
a carrier with a top surface separated from a bottom surface by a side surface;
a stator assembly attached to said carrier and including an exposed bottom surface;
a deflection cavity disposed in said carrier between said top surface and said stator assembly; and
a first fluid passage disposed in said carrier and extending between said top surface and said bottom surface; and
a second fluid passage disposed in said carrier and extending between said top surface and said side surface.
4. (original) The carrier of claim 3 wherein a portion of said second passage is defined by an annular valve seat;
said side surface includes a pair of annular ridges; and
said second passage opens through said side surface between said pair of annular ridges.